

HLL LIFECARE LIMITED, KANAGALA

ANNEXURE

WORK : Replacement of doors at Non-Steroidal plant

Sl. No.	Description	Unit	Qty	Rate	Amount
1	<p>GMP Single Door Size: 1000 x 2100. with Both side key operated locking arrangement , Automatic door bottom seal at the bottom & Stainless Steel kick plates CLEAN ROOM DOORS</p> <p>Providing & fixing of Doors designed to fit flush into the wall panel system on both sides. Doors are fabricated from galvanized iron sheets duly powder coated. Shutter has sheet thickness of 0.8mm and the frame of 1.2mm. Standard 50 mm panel has frame width of 50 mm and shutter width of 46mm.</p> <p>The following accessories are a part of the door:</p> <p>a)Shutter Thickness: 46 mm thick b)Stainless steel hinges c)Stainless Steel 'D' type of handles on pull side d)Stainless steel push plates on push side. e) Dorma / geze make standard arm door closure (TS-68) f)View panel along with self adhesive tape and silicon sealant g)Filler material : Puff</p>	Nos	2		
2	<p>GMP Single Door Size: 1200 x 2100. with Both side key operated locking arrangement , Automatic door bottom seal at the bottom & Stainless Steel kick plates CLEAN ROOM DOORS</p> <p>Providing & fixing of Doors designed to fit flush into the wall panel system on both sides. Doors are fabricated from galvanized iron sheets duly powder coated. Shutter has sheet thickness of 0.8mm and the frame of 1.2mm. Standard 50 mm panel has frame width of 50 mm and shutter width of 46mm.</p> <p>The following accessories are a part of the door:</p> <p>a)Shutter Thickness: 46 mm thick b)Stainless steel hinges c)Stainless Steel 'D' type of handles on pull side d)Stainless steel push plates on push side. e) Dorma / geze make standard arm door closure (TS-68) f)View panel along with self adhesive tape and silicon sealant g)Filler material : Puff</p>	Nos	1		

3	<p>GMP Double Door Size: 1300 x 2100. with Both side key operated locking arrangement , Automatic door bottom seal at the bottom & Stainless Steel kick plates</p> <p>CLEAN ROOM DOORS</p> <p>Providing & fixing of Doors designed to fit flush into the wall panel system on both sides. Doors are fabricated from galvanized iron sheets duly powder coated. Shutter has sheet thickness of 0.8mm and the frame of 1.2mm. Standard 50 mm panel has frame width of 50 mm and shutter width of 46mm. The following accessories are a part of the door:</p> <p>a)Shutter Thickness: 46 mm thick b)Stainless steel hinges c)Stainless Steel 'D' type of handles on pull side d)Stainless steel push plates on push side. e) Dorma / geze make standard arm door closure (TS-68) f)View panel along with self adhesive tape and silicon sealant g)Filler material : Puff</p>	Nos	4		
---	--	-----	---	--	--

Contractor sign with seal