

## HLL PHARMACY AT AIIMS, NEW DELHI

## INTERIOR WORKS SUMMARY

S.No.	DESCRIPTION	Amount (in Rs)
A	DISMANTLING	-
B	MASONARY & PLASTER	
C	FLOORING & CLADDING	-
D	PARTITION & PANELLING	-
E	CEILING	-
F	DOORS&HARDWARES	-
G	FIXED STORAGES	-
H	LOOSE FURNITURES	-
I	PAINTING & FINISHING	-
J	MISCELLANEOUS	-
K	SUPPORT SERVICES	-
	<b>TOTAL</b>	<b>-</b>

HLL PHARMACY AT AIIMS, NEW DELHI					
BILL OF QUANTITIES FOR CIVIL & INTERIOR WORKS					
S.NO.	ITEM	UNIT	QTY	RATE	AMOUNT
	<b>WET WORKS</b>				
<b>A</b>	<b>DISMANTLING</b>				
1.00	<b>DISMANTLING OF Existing CEILING</b> :- Dismantling of existing ceiling grid, ducts and handed over to store within 1KM ; store existing ceiling tiles at site for reuse as directed by project managers.	SQM	529.74		
2.00	<b>DISMANTLING OF Existing AL WINDOWS PANES</b> :- Dismantling of existing Aluminium window panes and glass further hand over to store within 1KM as directed by project managers.	NOS	14.00		
3.00	<b>DISMANTLING OF Existing DOORS &amp; FRAMES</b> :- Dismantling of existing doors and door frames and hand over to store within 1KM as directed by project managers.	NOS	3.00		
	<b>TOTAL- DISMANTLING</b>				
<b>B</b>	<b>MASONRY &amp; PLASTER</b>				
1.00	<b>POLISHING OF EXISTING FLOORING</b> :- Repairing and polishing of existing kota stone flooring of minimum of 3 coats	SMT	530		
2.00	<b>CEMENT PLASTER</b> :- Providing and laying 12to 15mm thick cement plaster of mix 1:4:2( 1cement:4 fine sand: 2 coarse sand) to all type of RCC work in line , level and plumb including smooth cement finish as directed including providing necessary bands, drip moulds groove and wire-mesh at all junction of walls and ceiling including racking the joints or roughening the RCC surfaces, necessary curing scaffolding etc. complete as directed and specified.	SQM	5		
3.00	<b>POP Punning (6mm-12mm)</b> : Providing and fixing Average 6mm to 12mm thick POP Punning over cement plaster in line & plumb finished smooth to receive paint.	SQM	275		
	<b>TOTAL-MASONRY &amp; PLASTER</b>				
<b>C</b>	<b>FLOORING / CLADDING</b>				
1.00	<b>CERAMIC TILE CLADDING</b> :P/F of Ceramic Tiles - 300X300 fixed with adhesive(veber/laticrete) or laid over 12mm thick cement mortar(1:4) including cutting of tile and finishing/Grout .The rate shall be inclusive of necessary preparation, cleaning, Make :Somany,Nitco,Kajaria,Finish:Matte(Basic rate: Rs.50/sqft)	SQM	15		
2.00	<b>STONE CLADDING</b> :Providing and Fixing of 300mm Wide ,19mm thick Stone cladding- Black Granite with plaster in both vertical and horizontal surface around door as/design.	RMT	8		
	<b>TOTAL:FLOORING /CLADDING</b>				
<b>D</b>	<b>PARTITIONS &amp; PANELLING</b>				
1.00	<b>WOODEN FRAME WORK</b> : P/F 50mmx50mm <b>Kail wood frame</b> (Seasoned,anti termite proofed) wood frame for paneling / partition in reception and other areas as per detailed drawing.	SQM	5		

HLL PHARMACY AT AIIMS, NEW DELHI					
BILL OF QUANTITIES FOR CIVIL & INTERIOR WORKS					
S.NO.	ITEM	UNIT	QTY	RATE	AMOUNT
2.00	P/F Framework using 12 mmx25mm Beech wood (Seasoned,anti termite proof) Member in Straight profile,melamine polished .	RM	5		
3.00	<b>PARTITION:-</b> P/F of 12mm thick magnesium Panel of size 1100x2400x10mm on both sides of 50mm thick Aluminium (CC50)-Box section Frame work to be fixed at every 610mm/c both horizontally and vertically .Frame to be fire proof coated. Base panel with humidity resistance of 99 RH. The cavity of studd framework should be filled with Glass-wool having 48 kg/m3 in stud cavity. This system having fire rating of 2.5 hrs as per EN13501 - 1 and noise isolation of 40 db as per ISO 140 - 3. The Tufbloc Panel is Water Resistance having Humidity Resistance of upto RH99 .Joints to be flushed with jointing taping without any undulation.(Rate/include - Two side board,insulation,Include-AL frame work). <b>Make: Anutone-Tufbloc Panel/Rockwool, Twiga- insulation</b>	SQM	270		
4.00	<b>PLYWOOD LAYER:</b> P/F of 12mm thick BWP Ply fixed on relevant Frame Work(GI/Merandi Wood frame work).Make: Archid ply,Green ply,Donear,	SQM	100		
5.00	<b>PLYWOOD LAYER:</b> P/F of 12mm thick commercial Ply fixed on relevant Frame Work(GI/Merandi Wood frame work).Make:Archid ply,Green ply,Donear,	SQM	35		
6.00	<b>MDF LAYER:</b> P/F of 12 mm thick MDF complete with grooves as per detail finished with grooves in columns. Edges of MDF to be finished in the same finish match to main panel. Make:Archid ply,Green ply,Donear,	SQM	5		
7.00	<b>AL SKIRTING:</b> 50 MM HIGH ALUMINIUM SKIRTING WITH AL. STRIP COVER AND 10X10MM METALLIC GROOVE :- Providing and fixing 1.5 to 2mm thick 50mm high extruded anodized aluminium skirting as per IS standard pasted/fixd over Partition as per Architects approval. Make:Alloy, Jeb,Infra	RMT	55		
8.00	<b>LAMINATED SKIRTING:</b> P/F of 100mm x 12mm High Laminated skirting of approved colour/shade/design on 12mm thk comm.Ply with ABS edge band .The band to be fixed to surface with dry wall screws .Make:Merino,Donear,Green ply	RMT	135		
9.00	<b>BEADING:</b> P/F of Anodized aluminium strips -'T'/U' shaped. Make:Alloy/JEB/Infra L shaped trim-Make:Alloy-S.01(5x28)/JEB/Infra	RMT	125		
10.00	<b>QUARTZ LEDGES:</b> Providing and Fixing of 19MM commercial ply on framework as/designd shape pasted with 8mm thick quartz cladding,Marble to be laid , jointed and, grouted. Grinding, rubbing, mirror polishing etc to be executed as per details, specifications, drawings & pattern and to satisfaction of the Project Manager. Make:Asian Granito India Ltd-Avantura Martini,Ocean Maple/ Kalinga Stone,	SQM	35		
11.00	<b>PVC CLADDING:</b> Providing , Welding and cladding of 1.25mm thick PVC roll (1.83MX30M),Weight Group1:2120g/m*,the combination of PU cladding,adhesive and substrate should meet fire norms with minimum of 2 hrs retendancy. ISO 14644-11999 class 4 norms for clean room to be mainted. VOC emissions to be NIL. Light Fastness to be adhered. Make:Polyclad-Polyflor,Armstrong	SQM	175		
12.00	<b>GLASS PARTITION:G1:</b> P/F of fixed glazing .10mm thick tempered glass with cutting as/design shall be fixed with 4 side anodized Aluminium extrusions 100x18/90x25 both horizontal & vertical member as per manufactures standards . All joints and edges to be filled with silicon. Make:JEB/Alloy	SQM	65		

HLL PHARMACY AT AIIMS, NEW DELHI					
BILL OF QUANTITIES FOR CIVIL & INTERIOR WORKS					
S.NO.	ITEM	UNIT	QTY	RATE	AMOUNT
13.00	<b>GLASS WINDOWS:</b> P/F of fixed casement windows with unplasticized polyvinylchloride channels , giving 40% protection from heat with well insulated 6mm thick tempered glass as/Indian standard. Window to reduce sound intrusions upto 42 decibels. Profile of 2.5mm outer wall thick, compliance to EN12608 & BS 7413 lead free ,galvanized iron D section wall reinforced outer frame. Design to be approved by Architect..Hardware-Roto/LGF,Make:AIS,Fenesta	SQM	32		
14.00	<b>LEDGE</b> at Sill level: Providing and fixing of 18mm thick post-formed ledge of 230mm width fixed with relevant adhesives at sill and around windows as per architects approval.	RM	63		
15.00	<b>ACRYLIC CLADDING:-</b> Providing and Cladding of 10mm thick acrylic of approved shade over 12mm thick MDF surface fixed over hard wood framing including all hardware fire retardant paint etc in both horizontal and vertical surface .Joints to be thermoformed at 75mm dia and edges to be finished as/design. Make: LG - Perna White/ Merino-silverwhite	SQM	46		
16.00	<b>LAMINATED PANEL LAYER-P/F</b> of 1mm thick laminate on partition as/design. make:merino,Greenlam	SQM	5		
<b>Total-Partition &amp; Paneling</b>					
<b>E CEILING</b>					
1.00	<b>PLANK GRID CEILING:</b> Providing and fixing Perforated Aluminium panel hole of 2 mm diameter and 5 mm center to center apertures represents 15% perforated area, of approved colour consisting of panel 150/300 mm wide x 15.5 mm deep x 0.5 mm thick with bevel edge, panel length up to 2.4 mtr, Coil Coated on a Continuous Paint Line, Double baked and roll formed from enameled corrosion resistance aluminium alloy AA 5050 (Al. Mg) for higher strength and good roll forming characteristics. The Panels abut each other with a narrow V groove. Panel shall be clipped to a baked enameled aluminium Panel carrier of 32 mm wide x 39 mm deep x 0.95 mm thick in standard length of 5 mtr made of doubled baked enameled aluminium alloy AA 5050 (Al. Mg) black with cut outs to hold the panels in a module of 150 mm closed at a distance 1.00 mtr. Panel carrier shall be suspended by means of G.I. suspension rod 4 mm diameter and a Galvanized suspension spring clip at a distance of 1.7 mtr c/c  Paint Finish: Aluminium panels shall be chromatised for maximum bond between metal and paint, enameled twice under high temperature, one side with a full primer and finish coat the other side (inner side) with a primer coating and Skin Coat on a Continuous Paint Line.  Acoustic Felt (Optional): Non-woven felt made of glass-reinforced fibre glued over the perforation for sound absorption. Mode of Measurements: Measurements shall be wall to wall without any deductions for lights, diffusers, columns etc. Make:Hunter Douglas-Luxalon@150C,Alloy,Armstrong	SQM	265		

<b>HLL PHARMACY AT AIIMS, NEW DELHI</b>					
<b>BILL OF QUANTITIES FOR CIVIL &amp; INTERIOR WORKS</b>					
<b>S.NO.</b>	<b>ITEM</b>	<b>UNIT</b>	<b>QTY</b>	<b>RATE</b>	<b>AMOUNT</b>
2.00	<p><b>GRID CEILING</b> :P/F of only grid -15mm tagular to fix existing ceiling metallic 600x600 installation: To comprise main runner spaced at 1200mm centers securely fixed to the structural soffit using suspension system at 1200mm maximum center &amp; not more than 150mm from spliced joints. The First/Last suspension system at the end of each main runner should not be greater than 600mm from the adjacent wall. 1200mm long cross tees to be interlocked between main runners at 600mm center to form 1200 x 600 mm module. All Perimeter trim to be wall angles, secured to walls at 450 mm maximum centers</p> <p>SUSPENSION SYSTEM accessories manufactured and supplied , consisting of M6 Anchor Fasteners with Vertical Hangers made of Galvanized steel of size 26 x 26 x 25 x 1.2mm .Straightened Hanger wire of dia - 2.68 mm of 1.83 m length., thickness with Adjustable hook clips of 0.8mm thick. The adjustable clip also consists of a 3.5 mm aquiline wire to be used with the main runner.Make:Armstrong,Hunter Douglas</p>	SQM	265		
3.00	<p><b>SUSPENDED SCREEN PELMET</b>:Providing and Fixing of Pelmet for Projection screen 1800mm high,150MM wide - 19mm thick comm board on both sides fixed and suspended from ceiling with relevant fasteners, Aluminium and hardwood framing. Boxing to be finished with 1mm thick laminate as/app Make:Merino/Greenlam</p>	RMT	11		
4.00	<p><b>BLACK PAINTED PLY</b>:-Providing and fixing black painted 6mm thick commercial ply over hard wood framing covering existing ventilator and windows</p>	SQM	33		
5.00	<p><b>TRAP DOOR</b>:Providing and Fixing of Trap Doors-Laminated trap door (Off White/match to ceiling color,with edge and angles powder coated in same shade) in Gypsum board Ceiling as per requirement.</p>	SQM	6		
6.00	<p><b>PLY BACKING</b>:Providing and fixing 6mm thick. commercial ply backing on mineral fiber modular false ceiling tiles to support light fitting, speakers, CCTV cameras, diffuser of grid work size with necessary cut outs for the same.</p>	EACH	15		
7.00	<p><b>LIGHT SUPPORT</b>:50X50X3MM THICK MS ANGLE FOR CEILING LIGHT SUPPORT:-Providing and fixing 50x50x3mm MS angle in U shape screwed with 125x125 pelmet in commercial ply to receive the ceiling light wherever AC ducts are coming.</p>	EACH	25		

HLL PHARMACY AT AIIMS, NEW DELHI					
BILL OF QUANTITIES FOR CIVIL & INTERIOR WORKS					
S.NO.	ITEM	UNIT	QTY	RATE	AMOUNT
8.00	<p><b>UNDER DECK INSULATION:</b> Under-deck insulation should be done with glass wool having 48 Kg/m<sup>3</sup> density and 70 mm thickness suitably installed so that the overall Thermal transmittance or U-value should be less than 0.409 W/sq.m.K to conform ECBC-2007 requirement. The insulation should conform to non-combustibility, Class-P(not easily ignitable), Class 1(surface spread of flame NIL), as per BS 476 standards. Installation:•The ceiling surface is thoroughly cleaned.</p> <p>•Fix soffit / clamp to ceiling by means of rawl plug/ dash fasteners. •Fix Z or C shaped GI channel runners or aluminium ones along the length of the room at 600mm spacing in one direction to the ceiling by rawl plugs/dash fasteners. Apply any suitable adhesive to the ceiling and place slabs of Fiberglass insulation in between by spot sticking method. •Hold the insulation slab in position by 22 SWG GI lacing wire placed diagonally. •Apply 12 mm Gypboard or equivalent plaster board to cover up the insulation. Make:Twiga,Rockwool</p>	SQM	530		
	<b>TOTAL:CEILING</b>				
<b>F</b>	<b>DOORS &amp; HARDWARES</b>				
	Note:Unless specified the door frame rates not be included. Rates to include door shutter,Hardware,and fitting charges. Framework--Make-Ozone,Wood-Make/Greenply,				
1.00	<p><b>TYPE D1:(2400X2400)</b> Double leaf glass door made of 10mm thick tempered glass with all round beading, Alloy partition system aluminium horizontal and vertical member 18x100. The rate should be inclusive of all hardware Ozone upper patch bottom patch , Ozone make door handle OGH 55(25x600)/PSS/SSS-H shape , Ozone make floor spring FS 8400, floor lock , strike plate &amp; EP cylinder, 10X10 mm Aluminium 'u' groove to be used as shadowline around the door frame etc complete as per design and drawing. (Main Door)</p>	NOS	1		
2.00	<p><b>TYPE D2:(1200X2400)</b> Single leaf glass door made of 10mm thick tempered glass with all around Aluminium beading, Partition system aluminium horizontal and vertical member 18x100. The rate should be inclusive of all hardware Ozone upper patch bottom patch , Ozone make door handle OGH 55(25x600)/PSS/SSS-H shape , Ozone make floor spring FS 8400, floor lock , strike plate &amp; EP cylinder, 10X10 mm Aluminium 'u' groove to be used as shadowline around the door frame etc complete as per design and drawing. (Rear Door,Store entry)</p>	NOS	2		
3.00	<p><b>TYPE D3:(900X2400)</b> Single leaf glass door made of 10mm thick tempered glass with all around Aluminium beading, Partition system aluminium horizontal and vertical member 18x100. The rate should be inclusive of all hardware Ozone upper patch bottom patch , Ozone make door handle OGH 55(25x600)/PSS/SSS-H shape , Ozone make floor spring FS 8400, floor lock , strike plate &amp; EP cylinder, 10X10 mm Aluminium 'u' groove to be used as shadowline around the door frame etc complete as per design and drawing. (Office,delivery entry)</p>	NOS	3		

HLL PHARMACY AT AIIMS, NEW DELHI					
BILL OF QUANTITIES FOR CIVIL & INTERIOR WORKS					
S.NO.	ITEM	UNIT	QTY	RATE	AMOUNT
4.00	<b>ROLLING SHUTTER:</b> Supply,installation testing and commissioning of factory fabricated modular type Aluminium rolling shutter with extruded aluminium channels of the size and design as approved by architect including all supports complete as required	SQM	12		
5.00	<b>DOOR FRAME:</b> P/F Door Frame -Beech wood 75x50mm thick ,seasoned,anti-termite proof,finished with duco paint in lacquer finish	Rm	5		
	<b>TOTAL-DOORS &amp; HARDWARES</b>				
<b>G</b>	<b>FIXED STORAGES</b>				
1.00	<b>FULL HT STORAGE:</b> P/F of pre-laminated storage unit of 18mm thick prelam board ,PVC edge banding as/dsgn.18mm thick prelam board hinged shutter with laminate and handle with individual locks.6mm thick laminated ply as backing of the unit along with 18mm thick prelam board as adjustable shelves. Size:2400 H x 900Wx600D <b>Make:Unicos/Featherlite</b>	Nos	6		
2.00	<b>MEDIUM HT STORAGE:</b> P/F of pre-laminated storage unit of 25mm thick prelam board top , pvc edge banding as/dsgn.18mm thick prelam board hinged shutter with laminate and handle with individual locks.6mm thick laminated ply as backing of the unit along with 18mm thick prelam board as adjustable shelves. Size:1200 H x 900Wx600D <b>Make:Unicos/Featherlite</b>	Nos	5		
3.00	<b>MEDICINE STORAGE:</b> P/F of 2400MM HIGH 650MM wide pre-laminated storage unit as/design. 25mm thick prelam board top with to be provided at 450mm ht ,18mm thick prelam board hinged shutter with laminate and handle with individual locks upto 450mm height.6mm thick laminated ply to be used as backing of the unit along with 18mm thick prelam board as adjustable shelves. Two units to be fixed on 450mm high storage unit,each of 1950mm high 300mm wide with pigeon holes of size 300mmx300mm ,with 12mm thick pre-laminated vertical and horizontal boards. Every alternate horizontal member to fixed on adjustable screws as/design. Size:2400Wx450Hx650D+2nos(2400Wx1950Hx300D) <b>Make:Unicos/Featherlite</b>	Nos	14		
4.00	<b>OFFICE FURNITURE:</b> Modular Workstation 1500mm x 1500mm .50mm thick ,1200mm high main screen with powder coated trims ,magnetic fabric panel and writing board above table top and laminated panel below work top. Side screen of fabric above table top and laminate below table top. Relevant raceways one at skirting level and one above table top to be provided. Table top-25mm thick pre-laminated Worktop with 2 +1 filling drawer , <b>Make:Unicos/Featherlite</b>	Nos	4		
5.00	<b>LAMINATED COUNTER:</b> P/F of 25mm thick,1050 wide post formed top fixed with 450mm long powder coated brackets as/ per Architects approval <b>Make: Unicos, Featherlite</b>	NOS	24		

HLL PHARMACY AT AIIMS. NEW DELHI					
BILL OF QUANTITIES FOR CIVIL & INTERIOR WORKS					
S.NO.	ITEM	UNIT	QTY	RATE	AMOUNT
6.00	<b>ELECTRICAL D.B. CUPBOARD:-</b> Providing & fixing 600mm deep & 2100mm high cupboard for D.B. panel cabinets comprising shutters constructed from 20mm thick. comm. board finished in 1mm thick. laminate val, comprising of carcass constructed from 19 mm thick. Bison Board all inside , 6x20mm melamine polished Beech Wood lipping & 12x50 melamine polished white Beech Wood trims. Provide 150x300 powder-coated aluminum louvered grilles on each shutter, requisite cutouts for ventilation above and servicing trap door below. Rate should be inclusive of necessary Hardware- 294high H shaped Hettich handle code no.045711, , Lock sets, self-closing hinges, spring loaded shutter latch inside, all cabinet hardware to be of approved make & as/Architects approval.	SQM	9		
	<b>TOTAL:FIXED STORAGE</b>				
<b>H</b>	<b>LOOSE FURNITURE</b>				
1.00	<b>RECEPTION COUNTER:</b> P/P of Reception Counter: Double level Counter in elliptical shape of size 2100Lx2100W.Counter top at 1050mm level-12mm thick/60mm H acrylic cladding with framework as/dsgn Curved Frosted Toughened glass fixed with 30mm Dia SS Pipes. Two pedestal Unit,with One standard Drawer Unit and one file shutter as/dwrg. Facia to be finished with 1mm thick laminate and 3M dinoc lettering of brand as/dsgn.10mm thick SS 'U' groove to be used as/dsgn. All edges to be treated in same finish. Make:Green lam/Greenply/LG/Alloy	NOS	1		
2.00	<b>GRANITE COUNTER:-</b> Providing and placing 600MM wide, 2100mm length free standing Granite counter -19mm thick black granite on 12mm thick commercial ply and relevant framing supported by two 60mm dia chrome pipe with 12mm thick 500mm dia circular base plates of height 900mm .	Nos	1		
3.00	<b>WAITING SEATS:</b> P/F of waiting seats- 3 seater 4 armrest, seat/back- numerical control hydraulic molding of high quality cold rolling steel plate edges strengthened and decorated by die-casting Aluminium .Arms/Legs-Die casting molding of high strengthened aluminium alloy Coating- Electrostatic coating after rust proof treatment and electroplated polishing. Sponge- cold consolidation and foam facing high density and super soft PU. Make: Multiseats,Geeken,	NOS	48		
	 <p>● 5360</p>				

HLL PHARMACY AT AIIMS. NEW DELHI					
BILL OF QUANTITIES FOR CIVIL & INTERIOR WORKS					
S.NO.	ITEM	UNIT	QTY	RATE	AMOUNT
4.00	<b>OFFICE CHAIRS:</b> P/P medium back fabric chairs , ergonomic design, 5 pronged chrome plated finish base on twin wheel casters , with 3600 swivel Gas lift height adjustment, synchrotilt mechanism with locking facility having chrome arms fixed on cast aluminium frame. Color of upholstery as/app. Make:Unicos,Geeken	NOS	8		
					
5.00	<b>HIGH STOOLS :</b> P/P fabric seat /back , 5 pronged chrome plated finish base on twin wheel casters , with 3600 swivel Gas lift height adjustment,Color of upholstery as/app. Make:Multiseats/geeken	NOS	35		
					
6.00	<b>SLOTTED ANGLE RACK:-</b> Fabricating, supplying and placing slotted angle rack of size 900wx2100hx600deep with 4 nos of shelves as per architects approval	NOS	2		
	<b>TOTAL-LOOSE FURNITURES</b>				
<b>I</b>	<b>PAINTING &amp; FINISHING</b>				
1.00	<b>ACRYLIC EMULSION PAINT</b> -apply 3 coats in roller mode-paint with oxy rich 100% acrylic water base coating. Paint shall emit 90% less VOC,soft sheen,high scrub resistant,free from lead,mercury,chromium. Rate:include base preparation as/site conditions. Make:Spectrum-Resana,Berger	SQM	410		
2.00	<b>DUCO Paint</b> Providing and applying Duco paint finish on existing columns at site. as directed including necessary base work, preparatory work. Make:ICI,Dulux	SQM	5		

<b>HLL PHARMACY AT AIIMS. NEW DELHI</b>					
<b>BILL OF QUANTITIES FOR CIVIL &amp; INTERIOR WORKS</b>					
<b>S.NO.</b>	<b>ITEM</b>	<b>UNIT</b>	<b>QTY</b>	<b>RATE</b>	<b>AMOUNT</b>
3.00	<b>EXTERIOR PAINT:</b> Providing and applying acrylic aggregate textured wall coating in non-pigmented Permasan finish maintaining material consumption rate of average 3.25 Kg. per m <sup>2</sup> and 2 mm. to 2.5 mm. thickness on exterior of the building. Old, flaking, plaster of paris, gypsum and highly absorbent surfaces and those already finished with lime or distemper should be brushed down and then treated with a coat of Sealer mixed with water in the ratio 1:3 (Sealer one part, water three parts) and applied by a brush. Undulations, broken edges, minor imperfections / irregularities should be rectified by using a paste made of Rectochem Surface Improver mixed with ordinary Portland cement in the ratio of 1:1.Application By SS Trowel and Plastic Trowel. Film Thickness 2 mm. to 2.5 mm. Consumption Rate 3 to 3.5 Kg. Per Sq. Mtr. Average Shade Life Permanent - ( no pigments to be used).Adhesion Virtually permanent,Textures Non-Pigmented, Mild Textures, With Fine Circular, Cavity & Vertical Cavity. Make:Spectrum,Asian	SQM	250		
	<b>TOTAL-PAINTING &amp; FINISHING</b>				

HLL PHARMACY AT AIIMS. NEW DELHI					
BILL OF QUANTITIES FOR CIVIL & INTERIOR WORKS					
S.NO.	ITEM	UNIT	QTY	RATE	AMOUNT
<b>J</b>	<b>MISCELLANEOUS</b>				
1.00	<b>FROSTED FILM:</b> P/A of Anti glare -Dusted and frosted FILM to look like sandblasted or etched glass, Permanent, pressure-sensitive films to have transparent synthetic liner for easy cutting of logos or designs. Make:3M,Garware(Rates to include all delivery at site,installation & Relevant taxes)	SQM	10		
2.00	<b>VINYL CLADDING:</b> P/F of 0.2mm thick flexible PVC films cladded on gypboard/wall with relevant water based/solvent based adhesive Make:3M Di Noc-single color PS/ Garware	SQM	5		
3.00	<b>PRINTER LEDGES:</b> P/F of 3mm thick 250mm wide 450mm length Stainless steel ledges suspended and screwed by Stainless steel strings as per architects approval and design.	Nos	8		
	<b>TOTAL-MISCELLANEOUS</b>				
<b>K</b>	<b>SUPPORT SERVICES</b>				
1.00	Deployment of Security Personnel 24X7 to ensure Proper Fire Safety and Security during the Construction Period upto handing over.	units	1		
	<b>TOTAL-SUPPORT SERVICES</b>				