

HLL LIFECARE LIMITED, KANAGALA
Annexure

Sl. No.	Description	Unit	Qty	Rate	Amt
1	Providing, fabricating, assembling & fixing in position, anodized aluminium partition using aluminium sections of mat finish or glassy finish in combination of plain grove, single grove and double grove as per requirements for the frames of overall sizes 63.50mm X 38.10mm X with thickness of 2mm. having section weight, plain section 1.054 kg/m, single grove thickness 1.95mm, section weight 1.094kg/m, double grove thickness 1.9mm section weight 1.094kg/m as per requirement for frame, bottom member of 114.3mm X 44.45mm. thickness 3.18mm. weight 2.646kg/m: aluminium louvres section of size 36.5mm X 34.93mm. thickness 1.45mm. weight 0.429kg/m; bottom portions provided with 12mm thick prelaminated sheet (Nova pan sheet) both sides of approved colour lamination exterior grade upto 0.9m height, spacing of vertical member not exceeding 1.0 m c/c; sections are cut to the required lengths, joints mitred & corners grinded subdividing frames tenoned & riveted to the frames; the assembled frames stiffened with corner angles, stripped and fixed with screws, rawl plugs and teak wood guttas to RCC columns or masonry on side, RCC lintels or beams at top & floor at bottom; including cutting, chistelling & making good with cement mortar to match the original surface providing & 5.50mm thick plain glass or mat finish as required, at top portion viz., 0.9 to 2.13m. the glass and panels fitted with glazing clips of 19.00mm X 17.30mm of thickness 0.90 mm. weight 0.124kg/m, aluminium sections treated for removal of any rust and prevention of further rust formation, coated with greasy materials for non-adherence of mortars or any other sticky materials; vertical members embedded in the flooring by making suitable sized holes and fixing with cement mortar, with necessary opening for fixing of door of standard size (excluding cost of door) all the frame thoroughly cleaned, free from, rust scale or dirt including cost of material, labour, fixtures and HOM of machinery complete as specification. (Make : Jindal section & glass: Modi Float/Saint Gobain)	Sqm	47.00		
2	do-Using aluminium section Powdered coated to a minimum of 60-70 microns with exterior durable pure polymer grade powder of approved quality.	Sqm	42.00		
Total amount					

Contractor **sign with seal**