

SCHEDULE 2- Annexure 1

Technical Specification(Supply and installation of IP Based CCTV Surveillance system at HLL-CSEZ,Kakkanad)			
Sl.No	Item Description	UNIT	QTY
1	2 MP Fixed Turret Network Dome Camera(IP DOME Camera) , Efficient H.265+ compression technology, Clear imaging against strong back light due to DWDR technology, EXIR 2.0: advanced infrared technology with long IR range. (Make: HikVision) & 4X4 White Colour PVC BOX for fixing Cameras	No.	10
2	2 MP Fixed Turret Network Bulet Camera (IP Buller Camera) , Efficient H.265+ compression technology, Clear imaging against strong back light due to DWDR technology, EXIR 2.0: advanced infrared technology with long IR range. (Make: HikVision) & 4X4 White Colour PVC BOX for fixing Cameras	No.	5
3	32-ch 1U K Series AcuSense 4K NVR, Up to 32-ch IP camera inputs, H.265+/H.265/H.264+/H.264 video formats, Up to 1-ch@12 MP or 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity, Up to 256 Mbps incoming bandwidth. (Make: HikVision)	No.	1
4	24 Port Gigabit Unmanaged POE Switch 24 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports, IEEE 802.3at/af standard, 6 KV surge protection for PoE ports. (Make: HikVision)	No.	2
5	HDD : Purple series 8TB SATA Surveillance Hard disk. (Make: Western Digital)	No.	2
6	SFP : (DN001GSMLCD040CCNSFP) DNC- 1.25 Gbps, Single Mode, LC, duplex Type, 20 Km Supporting, Tx-1310nm / Rx-1310nm , Normal SFP Module	No.	4
7	WM Fibre Patch panel : 8 Fiber, SC Adaptor Simplex type, White color, ABS Material,IP55 Standard Wallmount Patch panel (without Adaptor and Pigtail) (H-245, W-205, D-65)	No.	2
8	Adaptor : SC/PC-SC/PC, Single mode, Simplex, With Flange, Blue Color Adaptor	No.	4
9	Pigtail : SC/PC, Single Mode (9/125µm), Simplex, 900µm Blue cable, 1meter, LSZH Pigtail	No.	4

10	Patch Cord : LC/PC-LC/PC, Single Mode(9/125µm), Simplex, Unarmoured, 2.8mm Yellow Cable, 3 Meter, LSZH Patch cord	No.	4
11	9u Rack : 9 U wall Mounting Rack, Metal Cable Manager - Black Fine Tex., Single Fan For WallMount with required accessories like wall mounting hardware packet,fan , cable manager etc (Make: Valrack)	No.	1
13	LEGRAND Power Distribution Unit - 06 Amp Universal - 04 Socket - Switch with Indicator - 06 Amp Fuse - 06 Amp 3 Pin Plug with Power Cable 0.75 sq.mm 1.5 meter Length - Black	No.	1
16	Cat 6 UTP loaded 24 Port patch panel . RJ 45 modules are suitable for 22 to 26 AWG solid wire terminations. (Make; ComScope)	No.	2
17	Cat6 UTP RJ45 Jack , Suitable for 22-26 AWG, both stranded and solid wires. (Make;ComScope)	No.	25
18	Cat6 UTP 1 Mtr. Patch cords with 8P8C RJ 45 modular plugs at both sides. (Make; ComScope)	No.	15
21	OFC : Supply of 6 Core, Single Mode (9/125um), 8mm, Unitube, CMP Jacket Type, Black Color OFC <i>(Approximate Quantity,Billing on actuals.)</i> (Make: Comscope)	Meter	100
22	CAT6 : Supply of CAT6 DATA Cable <i>(Approximate Quantity,Billing on actuals.)</i> (Make: Comscope)	Meter	1525
23	CAT6 Cable & OFC Laying Charges with Open white color PVC Conduiting through Wall/Floor/ Tray <i>(Approximate Quantity,Billing on actuals.)</i>	Meter	1625
24	Installation,Testing and Commissioning Charges of entire CCTV surveillance system	Lump	