

**SCHEDULE III-AMENDED****CIVIL & ELECTRICAL WORKS FOR SETTING-UP AMRIT PHARMACY  
OUTLETS AT HOSPITALS IN VARIOUS DISTRICTS OF ASSAM**

Item No	Details of items	Unit	Quantity	Rate	Amount
<b>A</b>	<b>CIVIL WORKS</b>				
<b>I</b>	<b>Structural Work</b>				
1	Clearing jungle including uprooting of rank vegetation, grass, brush wood, trees and saplings of girth upto 30 cm measured at a height of 1 m above ground level and removal of rubbish upto a distance of 50 m outside the periphery of the area cleared.	Sqm	30		
2	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil.	Cum	20		
3	Extra for every additional lift of 1.5 m or part thereof in excavation /banking excavated or stacked materials; All kinds of soil.	Cum	5		
4	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m	Cum	20		
5	Treatment of soil under existing floors using chemical emulsion @ one litre per hole, 300 mm apart including drilling 12 mm diameter holes and plugging with cement mortar 1 :2 (1 cement : 2 Coarse sand) to match the existing floor : With Chlorpyriphos/Lindane E.C. 20% with 1% concentrationSupplying chemical emulsion in sealed containers including delivery as specified Chlorpyriphos/ Lindane emulsifiable concentrate of 20% including Supply of chemical emulsion in sealed containers including delivery as specified Chlorpyriphos/ Lindane emulsifiable concentrate of 20%	Sqm	25		
6	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size	Cum	2.5		
7	Providing and laying in position specified grade of Reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement:1:1.5:3 (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size	Cum	3.5		
8	Centering and shuttering including strutting, propping etc. and removal of form for :Lintels, beams, plinth beams, girders, bressumers and cantilevers	Sqm	10		
9	Making plinth protection 50mm thick of cement concrete 1:3:6 (1 cement :3 coarse sand : 6 graded stone aggregate 20 mm nominal size) over 75mm thick bed of dry brick ballast 40 mm nominal size, well rammed and consolidated and grouted with fine sand including finishing the top smooth	Sqm	10		
10	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete Thermo-Mechanically Treated bars.	Kg	200		

Item No	Details of items	Unit	Quantity	Rate	Amount
11	Random rubble masonry with hard stone in foundation and plinth including levelling up with cement concrete 1:6:12 (1 cement : 6 coarse sand : 12 graded stone aggregate 20mm nominal size) upto plinth level with :Cement mortar 1:6 (1 cement : 6 coarse sand).	Cum	15		
12	Brick work in cement mortar 1:4 (1 cement : 4 coarse sand)with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in :	Cum	20		
13	Half brick masonry with common burnt clay F.P.S. (non modular) bricks ofclass designation 7.5 in superstructure above plinth level up to floor V level. Cement mortar 1:4 (1 cement :4 coarse sand)	Sqm	10		
14	Extra for providing and placing in position 2 Nos. 6mm dia. M.S. bars at every third course of half brick masonry.	Sqm	10		
15	Plastering with cement mortar 1:4,(1 cement: 4 fine sand) 12 mm thick one coat to the newly constructed wall for one side	Sqm	65		
16	Plastering with cement mortar 1:4,(1 cement: 4 fine sand)15 mm thick one coat to the newly constructed wall for one side	Sqm	60		
17	6 mm cement plaster of mix 1:3 (1cement : 3 fine sand) for slabs	Sqm	5		
18	Providing and fixing 18mm thick gang saw cut mirror polished premoulded and prepolished) machine cut for kitchen platforms, vanity counters, window sills , facias and similar locations of required size of approved shade, colour and texture laid over 20mm thick base cement mortar 1:4 (1 cement : 4 coarse sand) with joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels.Granite of any colour and shade;Area of slab over 0.50 sqm.	Sqm	10		
19	Providing edge moulding to 18mm thick marble stone counters, Vanities etc. including machine polishing to edge to give high gloss finish etc. complete as per design approved by Engineer-in-Charge.Granite work.	m	10		
20	Extra for fixing marble /granite stone, over and above corresponding basic item, in facia and drops of width upto 150 mm with epoxy resin based adhesive, including cleaning etc. complete.	m	10		
21	Providing & fixing glass panes with putty and glazing clips in steel doors, windows, clerestory windows including cutting and finishing for counters all complete. With minimum 5.5 mm thick glass panes.	Sqm	6		
22	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete:	Kg	500		
23	Providing corrugated G.S. sheet roofing including vertical/curved surface fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead and including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (up to any pitch in horizontal/ vertical or curved surfaces) excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.1.00mm thick with zinc coating not less than 275gm/m <sup>2</sup>	Sqm	50		

Item No	Details of items	Unit	Quantity	Rate	Amount
24	Providing and fixing 15 cm wide 45 cm overall semi-circular plain G.S. sheet gutter with iron brackets 40x3mm size, bolts, nuts and washers etc. including making necessary connections with rain water pipes complete.0.80mm thick with zinc coating not less than 275gm/m <sup>2</sup>	m	30		
<b>II</b>	<b>Furnishing/Renovation Work</b>				
1	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead	Sqm	20		
2	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer - in- charge.	Cum	1		
3	Demolishing brick work in cement mortar manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge.	Cum	2		
4	Dismantling steel work manually/ by mechanical means in built up sections without dismembering and stacking within 50 metres lead as per direction of Engineer-in-charge	Kg	5		
5	Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 metres lead:Of area beyond 3 sq. metres	Each	1		
6	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS : 15622 (thickness to be specified by the manufacturer ) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete.	Sqm	15		
7	Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick Cement Mortar 1:4 (1 Cement : 4Coarse sand) including pointing the joints with white cement and matching pigment etc., complete.	Sqm	25		
8	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	Sqm	120		
9	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface :	Sqm	120		
10	Wall painting two coat with premium acrylic emulsion paint of interior grade, having VOC (Volatile Organic Compound ) content less than 50 grams/ litre. of approved brand and manufacture, including applying additional coatswherever required to achieve even shade and colour.	Sqm	75		
11	Finishing walls with Acrylic Smooth exterior paint of required shade :New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm	Sqm	65		
12	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture.	Sqm	10		

Item No	Details of items	Unit	Quantity	Rate	Amount
13	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular and other section of approved make conforming to IS : 733 and IS : 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fastners including necessary filling up of gaps at junctions, at top, bottom and sides with required P.V.C/neoprene felt etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P brass/ stainless steel screws, all complete as per Architectural drawings and the direction of Engineer-in-charge (glazing and panelling to be paid for separately) :- Anodized aluminium sections .				
a)	For fixed portion	Kg	25		
b)	For shutters of doors, windows and ventilators including providing and fixing hinges /pivots and making provision for fixing of fittings wherever required including the cost of P.V.C / neoprene gasket required (Fittings shall be paid for separately) . Anodized aluminium sections	Kg	15		
14	providing and fixing 12 mm thick flat pressed decorative twin finished pre laminated board (both sides decorative super particle board exterior grade) approved variety of fire and moisture resistant, quality as directed by Engineer - charge (The pre laminated particle board conform to IS:12823) for partition instead of 5mm sheet glass in ( Item No 1&2) above. Full area of panels will be measured for payments	Sqm	10		
15	Providing and fixing float glass panes of 8 mm thickness at the counter with suitable Aluminium frames with EPDM rubber / neoprene gasket , providing opening for counters finishing of opening etc. complete for minimum 3 counters as per the directions of engineer-in-charge.	Sqm	12		
16	Providing and fixing anodised aluminium grill (anodised transparent or dyed to required shade according to IS: 1868 with minimum anodic coating of grade AC 15) of approved design/pattern, with approved standard section and fixed to the existing window frame with C.P. brass/ stainless steel screws @ 200 mm centre to centre, including cutting the grill to proper opening size for fixing and operation of handles and fixing approved anodised aluminium standard section around the opening, all complete as per requirement and direction of Engineer-in-charge. (Only weight of grill to be measured for payment).	Kg	5		
17	Providing and fixing aluminium tower bolts ISI marked anodised ( anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with nuts and screws etc. complete-150 X 10 mm	Each	1		
18	Providing and fixing aluminium handles ISI marked anodised ( anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with nuts and screws etc. complete-125mm	Each	2		
19	Providing and fixing special quality bright finished brass locks with four levers including necessary screws etc. complete (bestmake of approved quality) :65mm (For	Each	1		

Item No	Details of items	Unit	Quantity	Rate	Amount
20	Providing and fixing in wall lining medium density fibre board IS: 14587:1998 marked, Pre-laminated one side decorative lamination and other side balancing lamination, with necessary fixing arrangement and screws etc. complete as per design. 18mm thick	Sqm	5		
21	Supplying and fixing rolling shutters of approved make, made of required size M.S. laths, interlocked together through their entire length and jointed together at the end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength conforming to IS: 4454 - part 1 and M.S. top cover of required thickness for rolling shutters.80x1.20 mm M.S. laths with 1.20 mm thick top cover.	Sqm	10		
22	Providing and fixing ball bearing for rolling shutters	Each	4		
23	Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia & length ( hold fast lugs or dash fastener shall be paid for separately). Second class teak wood	Cum	0.1		
24	Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows, including ISI marked M.S. pressed butt hinges bright finished of required size with necessary screws, excluding panelling which will be paid for separately, all complete as per direction of Engineer-in-charge.Second class teak wood. 35mm thick shutters	Sqm	5		
25	Providing and fixing chromium plated brass 100 mm mortice latch and lock with 6 levers and a pair of lever handles of approved quality with necessary screws etc. complete	Each	1		
26	Providing and fixing tiled false ceiling of approved materials of size 595x595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanized steel sections ( galvanized @ 120 grams/ sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size 24x25 mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids of 600x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc. Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanised butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottom exposed width of 24 mm of all T-sections shall be pre-painted with polyester paint, all complete for all heights as per specifications, drawings and as directed by Engineer-in-charge				

Item No	Details of items	Unit	Quantity	Rate	Amount
	12.5 mm thick square edge PVC Laminated Gypsum Tile of size 595x595 mm, made of Gypsum plasterboard, manufactured from natural gypsum as per IS 2095 part I and laminated with white 0.16mm thick fire retardant PVC film on the face side and 12micron metalized polyester on the back side with all edges sealed with the face side PVC film which goes around and wraps the edges and is bonded to the edges and the back side metalized polyester film so as to make the tile a completely sealed unit	Sqm	25		
27	Slotted angle metallic rack made up of 40 X 40 X 3 mm size rolled steel Angle posts shall have 8-mm diameter holes provided at 50-mm centres. The holes shall start at 12.5 mm centres from each end. Metal shelves shall be made from mild steel sheets not less than 1.0 mm in thickness. Shelves shall have lipped flanges width of flange being 30 mm and depth of lip 15 mm and having 5 shelves or more .The center to center distance of posts shall not exceed 750mm in both directions. Bended portion should face upwards				
a	Of Size 2bX3lX8h (Feet)	Each	8		
b	Of Size 1.3bX4lX8h (Feet)	Each	2		
28	Extra for covering open space in rack by providing and fixing perforated metal mesh of 1 mm thick cost of necessary fixing arrangement and screws etc. complete	Sqm	100		
29	Providing and sticking Frosted Crystal Glass Film on glass panes in partition , doors etc.	Sqm	10		

Item No	Details of items	Unit	Quantity	Rate	Amount
<b>B</b>	<b>ELECTRICAL WORK</b>				
1	Point wiring in PVC conduit, with Modular type switch: Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with modular switch, modular plate, suitable GI box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required	Point	14		
2	Power plug wiring in PVC conduit (2x4 sq mm) : Wiring for light/ power plug with 2x4 sq. mm FR PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit along with 1 No 4 sq. mm FR PVC insulated copper conductor single core cable for loop earthing as required	m	40		
3	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required.				
3.1	2 X 1.5 sq. mm + 1 X 1.5 sq. mm earth wire	m	30		
3.2	2 X 2.5 sq. mm + 1 X 2.5 sq. mm earth wire	m	20		
4	S/F PVC conduit : Supplying and fixing of 25MM size medium class PVC conduit along with accessories in surface/recess including cutting the wall and making good the same in case of recessed conduit as required.	m	25		
5	S/F Modular boxes, base & cover plate : Supplying and fixing 1 or 2 module ( 75 mmx75 mm),GI box along with modular base, cover plate for modular switches in recess etc as required.	Each	5		
6	S/F light plug point modular type accessories : Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 1 No. x 3 pin 5/6 amps modular socket outlet and 5/6 amps modular switch, connection,painting etc as required,	Each	5		
7	S/F Power plug point with modular type switch : Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 6 pin 15/16& 5/6 amps modular socket outlet and 15/16 amps modular switch, connection,painting etc as required.	Each	4		
8	Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 2 Nos. 3 pin 5/6 A modular socket outlet and 2 Nos. 5/ 6 A modular switch, connections etc. as required.	Each	6		
10	Supplying and drawing of UTP 4 pair CAT 6 LAN Cable in the existing surface/ recessed steel/ PVC conduit as required.	m	30		
11	Supply and Fixing of RJ 45 data outlet in existing modular box with connections complete.	Nos.	6		

Item No	Details of items	Unit	Quantity	Rate	Amount
12	6 way (4 + 18), Double door TPN DB Supplying and fixing following way, horizontal type three pole and neutral, sheet steel, MCB distribution board, 415 V, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without	Each	1		
13	8-way DB: Supplying and fixing following way, single pole and neutral, sheet steel, MCB distribution board, 240 V, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator) 8 way, Double door	Each	1		
14	S/F 'C' series, MCB : Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.				
14.1	Single pole	Each	20		
14.2	Single pole and neutral	Each	1		
15	Supplying and fixing following rating, four pole, (three phase and neutral), 415 V, residual current circuit breaker (RCCB), having a sensitivity current 30 mA in the existing MCB DB complete with connections, testing and commissioning etc. as required.	Each	1		
16	S/F 20A SPN MCB industrial socket outlet : Supplying and fixing 20 A, 240 V, SPN Industrial type socket outlet, with 2 pole and earth, metal enclosed plug top alongwith 20 A, "C" curve, SP, MCB, in sheet steel enclosure, on surface or in recess, with chained metal cover for the socket out let and complete with connections, testing and commissioning etc. as required.	Each	1		
17	Supply conveyance, installation, testing and commissioning the following types of light fittings with all accessories on false ceiling, true ceiling or wall as directed and giving connections with 16/0.20 mm 3 core PVC insulated and sheathed round copper conductor flex wire or extending the original wiring and giving connections as required. All recessed type fixtures are to be supported independently with chains or GI wire anchored to the ceiling with anchoring bolt of necessary size. All loose wires above the false ceiling are to be neatly concealed by flexible conduits.				
17.1	2 x 36 W CFL Square type ( 600 x 600mm) decorative recessed fitting complete with all accessorites ( Make : Bajaj BMLA 101 CFL)	Nos.	4		
17.2	1 x 15 W round recessed type LED – Philips Green LEDi900 – 4000K	Nos.	4		
17.3	1 x 36 W CFL fitting : surface mounting type CRCA precoated electronic box type luminaires with decorative end caps : Bajaj BCIR 136 or equivalent	Nos.	2		



Item No	Details of items	Unit	Quantity	Rate	Amount
18	Supply, Installation, testing and commissioning of ceiling fan (1200mm sweep), including wiring the down rods of standard length (upto 30 cm) with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable etc. as required. The Ceiling fan shall be double ball bearing type including step dimmer, all fittings and accessories complete. (Make : USHA, Crompton High breeze )	Nos.	1		
19	Supply, Installation, testing and commissioning of wall mount fan (400mm sweep), adjustable speed . min 60 degree oscillation, swing, Adjustable upward and downward tilt mechanism, Protective Guard, Including connections with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, mounting accessories, etc. as required. It shall be double ball bearing type .including step dimmer , all fittings and accessories complete. (Make : USHA, Crompton , Havells)	Nos.	2		
20	Supply and laying of following size 1.1 KV grade XLPE insulated, PVC sheathed, armoured Aluminium conductor power cable conforming to IS 7098 (Part 1) amended upto date.( including termination on both ends) 4C x 16 Sq.mm	m	30		
21	Supply, Installation, testing & commissioning of 3 phase 4 wire electronic type energy meter with LCD display with battery back up, class 1.00 CT with inbuilt CT. The whole unit to be mounted on suitable metal enclosure ( powder coated with locking arrangement, seperate enclosure for incoming and outgoing) with 3 Nos. HRC fuses, Neutral Link and all connections complete.	job	1		
22	Providing and fixing 4.00 mm dia copper wire on surface or in recess for loop earthing as required.	m	30		
23	Supply, installation, testing and commissioning of Air Cooled High Wall mounted Split Air Conditioner of following capacity consisting of high wall mounted type room unit (fan coil) with cordless remote control and one number outdoor condensing unit comprising of enegy efficient suitable rotary compressor for operation on single phase, 230 V, 50Hz supply, fixing the outdoor unit on a raised platform as per manufacturers recommendation and fixing of room (fan coil) unit on wall, standard 4 m distance refrigerant copper piping with 13mm nitrile rubber insulation, providing and making interconnection between room & condenser as per site conditions, comprising of 1" dia drain PVC pipe with insulation 4m, canvas connections, full electrical cabling from power plug near indoor unit and to outdoor unit, ODU MS stand, first charge refrigerant gas, suitable stabilizer etc complete as required. ( Make : Voltas , Blue Star, Hitachi, Carrier ) [ Coil : Copper ]				
	2 TR 5 star rated as per BEE	Nos	1		
<b>C</b>	<b>FIRE SAFETY :</b>				
1	Supply of ABC Type fire extinguisher of 2 Kgs. Make SAFEX / MINIMAX / CEASEFIRE or equivalent	Nos.	2		

Item No	Details of items	Unit	Quantity	Rate	Amount
<b>D</b>	<b>CCTV-SECURITY SYSTEM</b>				
	Supply ,Installation ,Testing & commissioning of the following items :				
1	Indoor IR Dome camera : 1/3" CCD or equivalent, 1.0 lux,AWB / BLC / AGC , min 20m range, Built-in IR illumination, white color case, PAL-CE/FCC approved., make CP PLUS or equivalent.	Nos.	2		
2	Outdoor IR Bullet camera : 1/3" CCD or equivalent ,1.0 lux,AWB / BLC / AGC , ,min 20m range,Built-in IR illumination, white color case, DC12V, PAL-CE/FCC approved., make CP Plus or equivalent	Nos.	1		
3	Power supply unit for above camera as specied by camera manufacturer -12VDC 10A	Nos.	1		
4	Digital Video Recorder : 4-Channel Embedded HD DVR, 400fps, Real-time, with 2 TB HDD and English OSD, 230VAC. Rate shall be inclusive of all accessories, BNC Connectors, cable terminations etc complete.	Nos.	1		
5	21" LED Color Monitors. make (LG/Samsung)	Nos.	1		
6	Supply and Laying of RG-6 Coaxial video cable with ISI marked PVC conduit including terminations with suitable BNC, etc complete. Make Technoflex/Neolex/Finolex	m	40		
<b>E</b>	<b>FURNITURE ITEMS</b>				
	Supply of the following as per Lab standards:				
1	Counter Height Bar stools :Revolving adjustable Chrome plated steel body chairs with resistance to the corrosion. Cushion Seat with Lift mechanism for Adjustment of height. Minimum height 750mm before expansion. Medium Back rest and arm rest. Item shall be of reputed make.	Nos.	3		
2	Work Table for Lab Administrator/Heads (Standard) Computer/office table made up of Prelaminated board 19mm thick with wood base material both side laminated with lockable drawer and cabinet on side , retractable keyboard tray, fornt and sides fully covered. Dimensions : 92l x 46b x 77h cm or nearest	Nos.	1		
3	Executive Chairs (Standard) Revolving adjustable type Medium height Back Office Chair with arm rest with back tilt and swivel mechanism constructed out of mild steel and high quality plastic.	Nos.	2		
<b>F</b>	<b>MISCELLANEOUS:</b>				
1	Supply and Installation of backlit flex board of approved size and design. The board shall be fabricated out of of GI metal fixed on MS angle supports fastened to wall/structure. Including electrical fittings, connections, all accessories, necessary coat of primer and enamel paint, complete. (size shall vary as per approved design and site conditions and will be paid as actuals)	Sqm	10		
	<b>TOTAL AMOUNT</b>				

I agree to complete the work as per the schedule at the rates quoted by me as above.

**BIDDER**